








## Highbays & Floodlights

Product code	Name	Size	Product Description	Part Description	Color	Gross Price
<b>Highbays</b>						
007600001	<b>BRISC 150W MAX.</b>	Ø 287mm H 150mm 1.9KG	MultiWatt 80/120/150W 150lm/W Max. 2250lm 3CCT 3000/4000/5500K, Ra>80 Wide Flood, 90Dgr Beamangle PF>0.95, 50/60Hz, AC220-240V IP65, IK10, 5Y Warranty	SAMSUNG SMD Led 150lm/W PHILIPS 1-10V Dimmable Driver ENEC Powercable 30cm w/ IP65 connector Aluminium Body & PC Lens Suspending Ring included	● Black	
	 <b>Multi Use, 1-10V Dimmable</b>					
<b>Accessoires</b>						
00100010	<b>BRISC SENSOR</b>		Optional Brisc Microwave Sensor	Screw-on Microwave Sensor	○ White	
00100001	<b>BRISC REMOTE</b>		Remote Control	Brisc Microwave Sensor Compatible Multiple parameter settings	○ White	
	 					
<b>Floodlights</b>						
007800001	<b>QUASAR 50W</b>	H 225mm W 192mm D 37mm 1.6KG	8.000lm, 50W 150lm/W Ra>80, PF>0.97 4000K, Wide Flood 90Dgr, IP65, IK08, 5Y Warranty	Lumileds SMD 150lm/W Lifud Driver ENEC Powercable 30cm w/ IP65 connector Aluminium Body & PC Lens	○ White	
	 <b>Especially for White building</b>					
007801001	<b>VARGAS 50W MAX.</b>	H 224mm W 263mm D 45mm 1.5KG	MultiWatt 25/35/50W 150lm/W 3CCT 3000/4000/5500K, Ra>80 Wide Flood, 90Dgr Beamangle PF>0.95, 50/60Hz, AC220-240V IP65, IK10, 5Y Warranty	Lumileds SMD 150lm/W Lifud Driver ENEC Low Ripple Powercable 30cm w/ IP65 connector Aluminium Body Tempered Glass	● Black	
	 <b>Installers' Favorite</b>					
007801002	<b>VARGAS 100W MAX.</b>	H 269mm W 315mm D 50mm 2.2KG	MultiWatt 50/75/100W 150lm/W 3CCT 3000/4000/5500K, Ra>80 Wide Flood, 90Dgr Beamangle PF>0.95, 50/60Hz, AC220-240V IP65, IK10, 5Y Warranty	Lumileds SMD 150lm/W Lifud Driver ENEC Low Ripple Powercable 30cm w/ IP65 connector Aluminium Body Tempered Glass	● Black	
	 <b>Installers' Favorite</b>					
007802201	<b>SENSO 50W MAX.</b>	H 225mm W 192mm D 37mm 1.4KG	MultiWatt 30/50W 120lm/W 3CCT 3000/4000/5500K, Ra>80 Wide Flood, 110Dgr Beamangle PF>0.95, 50/60Hz, AC220-240V IP65, IK08, 5Y Warranty	Lumileds SMD 120lm/W Royal Onboard Driver ENEC Low Ripple Powercable 30cm w/ IP65 connector Aluminium Body Tempered Glass	● Black	
	 <b>PIR Sensor</b>					

