

Recessed Ceiling Lights

Product Code	Name	Size	Product Description	Part Description	Color	Gross Price
005201014	 MULTI USE	SPOTLIGHT Ø 165mm	3000lm, 30W, 3000K, RA93	Royal COB Led	● Black	
005201011		TILT L 110mm	R9=63, 36° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 140mm	Low Ripple, PF >0.97	Powercable 2,5meter Gst18 Male Installed		
005201016	 MULTI USE	SPOTLIGHT Ø 165mm	3000lm, 30W, 3000K, RA93	Royal COB Led	○ White	
		TILT L 110mm	R9=63, 36° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 140mm	Low Ripple, PF >0.97	Powercable 2,5meter Gst18 Male Installed		
	 MULTI USE	SPOTLIGHT Ø 165mm	3000lm, 30W, 3000K, RA93	Royal COB Led	● Grey	
		TILT L 110mm	R9=63, 36° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 140mm	Low Ripple, PF >0.97	Powercable 2,5meter Gst18 Male Installed		
005305001	 MATCH WITH TRACKSPOTS	DOWNLIGHT Ø 185mm	3000lm, 30W, 3000K, RA93	Royal COB Led	● Black	
		CEDIA L 160mm	R9=63, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 145mm	Low Ripple, PF >0.97	Powercable 2meter Gst18 Male Installed		
005305002	 MATCH WITH TRACKSPOTS	DOWNLIGHT Ø 185mm	3000lm, 30W, 3000K, RA93	Royal COB Led	○ White	
		CEDIA L 160mm	R9=63, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 145mm	Low Ripple, PF >0.97	Powercable 2meter Gst18 Male Installed		
005305003	 MATCH WITH TRACKSPOTS	DOWNLIGHT Ø 185mm	3000lm, 30W, 3000K, RA93	Royal COB Led	● Grey	
		CEDIA L 160mm	R9=63, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 145mm	Low Ripple, PF >0.97	Powercable 2meter Gst18 Male Installed		
005301031	 EASY TO REPLACE	DOWNLIGHT Ø 215mm	1600lm, 16W, 4000K, RA80	SAMSUNG SMD Led	● Black	
		GLOBAL L 110mm	R9=50, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 195mm	Low Ripple, PF >0.95	Powercable 2,5meter Gst18 Male Installed		
005301032	 EASY TO REPLACE	DOWNLIGHT Ø 215mm	1600lm, 16W, 4000K, RA80	SAMSUNG SMD Led	○ White	
		GLOBAL L 110mm	R9=50, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 195mm	Low Ripple, PF >0.95	Powercable 2,5meter Gst18 Male Installed		
005301033	 EASY TO REPLACE	DOWNLIGHT Ø 215mm	1600lm, 16W, 4000K, RA80	SAMSUNG SMD Led	● Grey	
		GLOBAL L 110mm	R9=50, 85° Beam Angle	Royal Driver TÜV ENEC		
		⌀ 195mm	Low Ripple, PF >0.95	Powercable 2,5meter Gst18 Male Installed		
005102011	 PREMIUM FINISH	SPOTLIGHT Ø 88mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	● Black	
		ODEON L 85mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		
00209012	 PREMIUM FINISH	SPOTLIGHT Ø 88mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	○ White	
		ODEON L 85mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		
00209013	 PREMIUM FINISH	SPOTLIGHT Ø 88mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	● Grey	
		ODEON L 85mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		
005102023	 PREMIUM FINISH	SPOTLIGHT Ø 85mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	● Black	
		SENSE L 95mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		
005102024	 PREMIUM FINISH	SPOTLIGHT Ø 85mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	○ White	
		SENSE L 95mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		
005102025	 PREMIUM FINISH	SPOTLIGHT Ø 85mm	900lm, 10W, 2700K, RA93	Bridgelux COB Led	● Grey	
		SENSE L 95mm	R9=63, 38° Beam Angle	OSRAM TRIAC Dimmable Driver		
		⌀ 77mm	Low Ripple, PF >0.95	Powercable 10cm Installed		

